### **Product information**

The STX range of switch mode power supplies has been specifically designed for EN54 compliant fire systems. Available in either 1A, 2A, 5A versions they are certified to EN54-4:1997, A1:2002 & A2:2006. The units include intelligent battery charging using Elmdene's efficient EcoCharge technology, possess mains & battery monitoring with independent volt-free outputs and also feature battery deep discharge protection in the event of a prolonged mains failure. The inclusion of LED indicators provides quick diagnostics of the status of the power supply, while a variety of enclosures offer the installer a choice of standby battery backup options



# STX Range 24VDC EN54 PSU Range

#### Main Feature:

- 27.6V DC output
- Cost effective switch mode technology
- Energy efficient
- More efficient in operation
  - Saves power reducing power bills
  - Longer life in the field
  - Less prone to failure
- Intelligent battery charging and monitoring using Elmdene's EcoCharge technology
- Deep Discharge Protection
- Remote fault signaling
- Full rated current to load plus additional current for battery charging
- LED indication:
  - Mains status
  - Output fault
  - Battery fault
  - Charger fault
- Volt-free fault output -EPS: Mains fail
- Volt-free fault output PSU fault:
  - Battery fault
  - Charger fault
  - Loss of output
- Mains transient protection
- Color: Grey

Approvals Certified by UL (EN54-4:1997 +A1: 2002 +A2: 2006) CE Mark RoHS Compliant



# Manufacturer: Elmdene International Limited 3 Keel Close, Interchange Park. Portsmouth, Hampshire, PO3 5QD, UK


#### **Part Number**

P/N	Rating (A)	Max Battery size
STX2401-C-SEC	1A	2 x 12V 7Ah
STX2402-C-SEC	2A	2x12V 7Ah


STX2405-E-SEC	5A	2x12V 17Ah
3172403-L-3LG	JA	ZX   Z V     / / \

### **Technical Information**


- Main Input: 93-264V ac
- Output: 27.6 V dc
- Operating temperature -10°C to 40°C at 95% RH
- Product Dimensions (mm): 275H x 330W x 80D
- Product Dimensions (mm): 420H x 400W x 80D



# **Connection Wiring**



## Dimension (mm)



WARNING: ALWAYS FIT 2 BATTERIES and wire in series, the product will NOT work with a single 12 V battery

Securiton AG, Alarm and Security Systems Securiton d.o.o., Serbia Securiton Kft., Hungary Securiton (M) Sdn Bhd, Malaysia Securiton RUS, Russia www.securiton.com, info@securiton.com www.securiton.rs, info@securiton.rs www.securiton.hu, info@securiton.hu www.securiton.com, asia@securiton.com.my www.securiton.ru, info@securiton.ru

